

Brugarolas



Industrial Lubricants



HYDRAULIC FLUIDS FOR PLASTIC INJECTION MACHINERY

HYDRAULIC FLUIDS FOR PLASTIC INJECTION MACHINERY

Special oils for injection and extrusion plastic machinery, must fulfill a group of requirements and specifications to guarantee smooth functioning since the first moment the machine is turned on.

The life of the fluid, antiwear properties of the pump, and the hydraulic components, all are a key factors to guarantee high performance.

PRODUCTS



HYDRAULIC




- FLUID DRIVE HM – 46
- FLUID DRIVE B – 4
- BESLUX DIVOL HV – 46
- BESLUX DRIVE HLP/SC 46
- BESLUX DRIVE HV/SC 46

GUIDES



BESLUX LUDER 220

GREASES




G. A. N.238 (antiblocking – nozzle)

G. BESLUX FLUOR H – 2
(grease ejectors)



HYDRAULIC FLUIDS FOR PLASTIC INJECTION MACHINERY



FLUID DRIVE HM – 46

Hydraulic fluid with ISO HM and DIN HLP certification. Fullfills the basic functioning requirements of injector machine manufacturers.

Viscosity Index: 105

FLUID DRIVE B – 4

Hydraulic fluid with ISO HM and DIN HLP certification, with the same specifications and the product above. It has Viscosity Index improvers and is a multigrade product that allows to have a fixed viscosity, even in the most extreme high temperature situations.

Viscosity Index: 120

BESLUX DIVOL HV - 46

Hydraulic fluid with ISO HV and DIN HVLP certification. It becomes a multigrade due to the amount of additives. Allows the preparation and initial functioning since the moment the engine is turned on. In very cold seasons, there is no need to wait until the fluid becomes stable and the viscosity reduces. Viscosity Index: 150

BESLUX DRIVE HLP/SC 46

Hydraulic fluid with ISO HM and DIN HLP certification, without Zinc content. It has “ash free” additives.

This fluid has a very good filtering ability and keeps systems with Servo-pumps and Electro-pumps totally clean, without any sedimentation due to high temperatures and additive crashing.


Viscosity Index: >105

BESLUX DRIVE HV/SC 46

Hydraulic fluid with ISO HV and DIN HVLP certification. Without Zinc. It has “ash free” additives.

This fluid has a very good filtering ability and keeps systems with Servo-pumps and Electro-pumps totally clean

Viscosity Index: 150



APPLICATIONS DE LUBRICATING FLUIDS

APPLICATIONS

- Hydraulic central

- Columns

CONTACT COMPONENTS

- Pumps
- Filters
- Electro-pumps
- Proportional servo-pumps

- Guides



Camino de la Riera 36-44
Polígono Industrial Cova Solera
08191 Rubí (Barcelona)

Tlf: 93 588 31 00

Fax: 93 588 31 01

E-mail: comercial@brugarolas.com

Web: www.brugarolas.com